


HB L1 Series

Single Phase Hybrid

PV 4.6/5/6KHB-60, PV 4.6/5/6KHB-120



HIGH YIELD

- Max efficiency 97.3%, Battery efficiency 94%
- Max. Charge/Discharge Current 120A
- Reasonable energy control to increase the proportion of spontaneous use



HIGH RELIABILITY

- With BMS system to ensure high battery life
- Natural cooling design



INTELLIGENT MAINTENANCE

- Compatible with lead-acid batteries and lithium battery energy storage systems
- Remote configuration and upgrade

Model	PV 4K6HB-60	PV 4K6HB-120	PV 5KHB-60	PV 5KHB-120	PV 6KHB-60	PV 6KHB-120
Efficiency						
Max. efficiency (PV to AC)	97.3%					
Max. efficiency (BAT to AC)	94.0%					
Input (PV)						
MAX PV Power	9000W					
Max PV voltage	550V					
Max input current (input A/input B)	15A/15A					
Max short current (input A/input B)	20A/20A					
Start operating voltage	90V					
MPPT voltage range	90V-520V					
No. of MPPT trackers	2					
String per MPP tracker	1					
Input (BAT)						
Compatible battery type	Lithium-ion / Lead-acid					
Nominal battery voltage	48V					
Battery voltage range	40V-60V					
Max. charge/discharge current	60A/60A	120A/120A	60A/60A	120A/120A	60A/60A	120A/120A
Max. charge/discharge power	3000W/3000W	5000W/5000W	3000W/3000W	5000W/5000W	3000W/3000W	6000W/6000W
Lithium battery charge curve	Self-adaption to BMS					
Output (Grid)						
Nominal AC output power	4600W	4600W	5000W	5000W	6000W	6000W
Rated Apparent Power	4600VA	4600VA	5000VA	5000VA	6000VA	6000VA
Max. AC output apparent power	4600VA	4600VA	5500VA	5500VA	6000VA	6000VA
Max. AC output power (PF=1)	4600W	4600W	5000W	5000W	6000W	6000W
Max. AC output current	22A	22A	25A	25A	27.2A	27.2A
Rated AC voltage	220V / 230V					
AC voltage range	150V-300V (Adjustable)					
Rated grid frequency	50Hz / 60Hz					
AC frequency range	45Hz-55Hz/55Hz-65Hz (Adjustable)					
Grid connection	Single phase					
Power factor	> 0.99 @rated power (Adjustable 0.8 LD - 0.8 LG)					
THDI	<3% (Rated Power)					
Output (Back up)						
Nominal output voltage	230V					
Nominal output frequency	50Hz / 60Hz					
Nominal output power	3000W	4600W	3000W	5000W	3000W	6000W
Nominal output current	13A	20A	13A	21.7A	13A	26A
Transfer time	10ms (typ) / 20ms (max)					
THDV	<3% @100% R Load					
Protection						
Protection category	Class I					
DC switch	Support					
Anti-islanding protection	Support					
AC overcurrent protection	Support					
AC short circuit protection	Support					
DC reverse connection	Support					
Surge Arrester	DC Type III, AC Type III					
Insulation detection	Support					
Leakage current protection	Support					
PV overvoltage category	II					
AC overvoltage category	III					
General						
Max. operation altitude	4000m					
Noise emission	<35dB					
Ingress protection degree	IP65					
Operating temperature range	-25°C~60°C					
Relative humidity	0~100%					
Cooling concept	Natural Cooling					
Mounting	Wall bracket					
Dimensions (W*H*D)	515mm*485mm*175mm					
Weight	20Kg	25Kg	20Kg	25Kg	20Kg	25Kg
PV connection way	MC4/H4					
Battery connection way	Dedicated DC connector					
AC connection way (grid & back up)	Dedicated AC connector					
HMI & COM						
Display	LED+APP					
Communication interface	RS485/CAN (for BMS), RS485, USB, DRM/RS485 (for Meter), Optional: WiFi/GPRS/LAN					
Certification						
Grid	VDE-AR-N4105, IEC 61727/62116, AS 4777, EN 50549-1, G99, CEI 0-21, NRS 097-2-1					
Safety	IEC62109-1&2, IEC62040-1, IEC62477-1					
Warranty	10 Years					
Country of Original	China					

Remarks:

- The range of output voltage and frequency may vary depending upon different grid codes.
- Specifications are subject to change without advance notice.